Cardinal Scale Manufacturin		S.	
		RFD	
Br			
	HSDC		
DIGIT	AL HANGING	SCALE	
scale that incorp shut-off mode to makes it lightwei under conditions	DC is a full featured, b porates push button tare prolong battery life. Its ight and easy to use, but required of any portable want it - <i>where you nee</i>	e, a sleep moo aluminum all ut tough enou ole, hanging s	de, and an auto oy construction gh to stand up
CARDINAL HSDC	Model HSDC-20	Capacity 20 lb	Graduation .01 lb
	HSDC-50	50 lb	.02 lb
CARCITY usite t c. ife	HSDC-100	100 lb	.05 lb
# (m) + (m)	HSDC-200	200 lb	0.1 lb
Ju www.	HSDC-500	500 lb	0.2 lb
	HSDC-20K	20 kg	.01 kg
m))	HSDC-50K HSDC-100K	50 kg 100 kg	.02 kg .05 kg
E E	eatures and Specifica	0	.00 kg
Display Type:	1" high LCD		
Power:			
	e Weight:		
Operating Temperature: +14° to 104°F (-10° to +40°C) Zero: Established during setup and maintained			
∠ero:		•	
Auto Zero Range:	automatically	•	
•			
	nonvolatile m		
Tare:			
Annunciators:			low battery, over
	capacity	· · · · · · · · · · · · · · · · · · ·	, ·
Controls:		, tare, net, off	
Sample Rate:	1 - 12 samples	per second,	selectable
Optional Stainless Steel Produce	e Pan 12.5" dia x 5" d	deep; 8 qt (50	0 cu. in.) volumetric
•			



These scales meet all requirements of Handbook 44, issued by the National Institute of Standards and Technology and has been issued the Certificate of Conformance number 94-03.

Cardinal Scale reserves the right to improve, enhance and modify features and specifications without prior notice.