

## **GENERAL SPECIFICATIONS**

- EXTERIOR FINISH: STAINLESS STEEL FRONT, PAINTED GRAY SIDES
- EXTERIOR DIMENSION: WIDTH 1338.6mm(52.7") DEPTH 838.2mm(33") HEIGHT 2057.1mm(81")
- 3. INTERIOR FINISH: STAINLESS STEEL
- INTERIOR DIMENSION: WIDTH 1244.6mm(49") DEPTH 685.8mm(27") HEIGHT 1568.5mm(61.75")
- 5. INSULATION: FOAMED-IN-PLACE, CFC AND HCFC-FREE POLYURETHANE
- 6. DOOR: DOUBLE PANE, TEMPERED GLASS, SLIDING GLASS DOUBLE DOOR, KEY LOCK
- 7. SHELVES:GRAY-8 WIRE, EPOXY COATED, ADJUSTABLE IN 1/2" INCREMENTS
- 8. CASTERS: 4 STEM MOUNT
- 9. CONTROLLER: DIGITAL, FACTORY SET TO 4°C (39°F)
- 10. DEFROST: N/A
- 11. COMPRESSOR:1/3 HP, REFRIGERANT R 134A
- 12. ELECTRICAL DATA: 115V 60Hz / 8.8 AMPS
- 13. PLUG TYPE: NEMA 5-15P
- 14. TOTAL CAPACITY: 45 Cu.ft
- 15. TEMPERATURE RANGE: 1 TO 12°C
- 16. AVERAGE TEMPERATURE STABILITY: ± 3 °C
- 17. APPROVALS: UL/cUL
- 18. SHIPPING WEIGHT: 255KG (561 LBS).

Thermo Fisher
S C I E N T I F I C
275 AIKEN ROAD
ASHEVILLE, NC 28804

THE INFORMATION CONTAINED HEREIN IS THE PROPRIETARY DATA OF THERMO FISHER SCIENTIFIC. IT IS NOT TO BE REPRODUCED OR DISCLOSED IN WHOLE OR IN PART WITHOUT PRIOR WRITTEN CONSENT OF THERMO FISHER SCIENTIFIC. DO NOT SCALE THIS DRAWING.

REFRIGERATOR
GLASS DOOR,45 CuFt

| -    | -         | -    | SEE SHEET 1 | 3rd ANGLE<br>PROJECTION |              | DWG. NO.           |
|------|-----------|------|-------------|-------------------------|--------------|--------------------|
| REV. | ECN#      | DATE | DESCRIPTION | PROJECTION              |              | MR45SS-GARE        |
|      | REVISIONS |      |             |                         | SHEET 2 OF 2 | 2 1/11/4300 0/11/2 |